RUSTKLEAN

Lconstructionproducts

RUST REMOVER

RUSTKLEAN is a single component, clear liquid which has been formulated for application in areas where the removal of tightly adhering rust to steel is difficult and costly by mechanical means.

USES

RUSTKLEAN is used to anodically passivate the rusted surfaces of steel and provides a stable surface for subsequent concrete repair or application of protective coatings.

FEATURES

- Single component, ready to use
- No special tools required for application
- Reacts fast as it penetrates directly into residual rust
- Economical compared to mechanical methods of rust removals
- Easy to apply

TYPICAL PRODUCT CHARACTERISTICS

Appearance : Clear liquid Specific Gravity : 0.93 +/- 0.01

SURFACE PREPARATION

All surfaces must be free of oil, grease or loosely adhering materials. Loose rust must be removed by wire brush or abrasive disc or paper.

APPLICATION

Apply RUSTKLEAN with a brush onto the rusted steel. On large areas it may be sprayed. After application at least one hour is required for RUSTKLEAN to "work" before it can be flushed away by fresh water. In order to prevent further damage it is recommended to cover the steel with concrete and/or protective coating immediately.

COVERAGE

Approx. 20 m² per litre may vary depending on the intensity of the rust.

PACKING

4 litre can

STORAGE/SHELF LIFE

Keep away from direct sunlight and store under normal warehouse conditions. Take precaution in storing the product in safe place. The shelf life of the product is 6 months from the date of manufacturing provided it is stored in unopened factory packing. Keep away from naked flame.

TECHNICAL SERVICES

Technical assistance and information is available by calling Falcon Chemicals (L.L.C.) on specific application.

HEALTH AND SAFETY

RUSTKLEAN contains highly corrosive chemical. Do not get in contact with neat product. Use rubber gloves and safety goggles while handling the product. Avoid eye and skin contact. In case of eye contact wash immediately with plenty of water and seek medical treatment.

DISCLAIMER

Use this leaflet as a guide for the use of the product concerned. The information given is in accordance with latest technical developments. However, we cannot accept liability/responsibility for any work carried out with our materials, as we have no control over the method of application used or the condition of site involved.

ISSUE DATE: DECEMBER 2011

This technical specification supercedes all previous data sheets.



FALCON CHEMICALS L.L.C.

P.O.Box 2924 - Dubai., Tel: 00971 4 8801444/8801818 (Fax)